



## FLAG Bilge Paint

### PRODUCT DATA

---

#### **Description:**

One coat system for all internal surfaces, giving good resistance to oil, grease, salt water and fresh water.

#### **Area of use:**

Bilges, lockers, engine compartments.

#### **Substrates:**

Wood, GRP and Steel and Concrete

#### **Packing:**

1 litre

#### **Physical Constants:**

Colour:	Off White
Finish:	Satin
Volume solids:	60%
Theoretical spreading rate:	10 –12 sq.metres per litre
Flash point:	38°C
Specific gravity:	1.3
Dry to touch:	4 – 6 hours
Overcoating time:	16 hours

*\*The theoretical spreading rate has been calculated for the stated volume solids and dry film thickness. A practical spreading rate will depend on the actual dry film thickness, the nature of the substrate, and the relevant consumption factor. The physical constants are subject to normal manufacturing tolerances.*

#### **Application Details:**

Application method:	Brush Conventional spray Airless spray Roller
Thinner:	White Spirit
Cleaning of tools:	White Spirit

**Surface condition:** The surface should be stable, firm, dry and free of dust, sand, loose old paint, dirt, grease, oil and salt.

*Please refer to the Material Safety Data Sheet for further information.  
For additional guidance please contact your local Technical Sales Representative.*

---

**SAFETY:** Handle with care. Before and during use, observe all safety labels on packaging and paint containers, consult Material Safety Data Sheets and follow all local or national safety regulations.